



- NOTE: 1) HYDRO @ 260 PSIG. MIN.
 2) ALL FNPT ARE SA-182-304 S.S.
 3) UHA-51 (e)(2)(a) NO IMPACT TESTING.
 4) 2"R HAS 10"R

SHELL / HEADS	.1875" SA-240-304 S.S. 2:1 S.E.	30-VA-120-RP	REV.
	(.176" MIN.) - TRIM	304 S.S.	DATE: 12-14-11
	.1875" SA-240-304 S.S.	FOR: HANSON STANDARD	
		VERT. AIR TANK	
		SURFACE AREA = 33.8 SQ. FT.	
		INSIDE: PASSIVATE	
		OUTSIDE: BEAD BLAST AND PASSIVATE	
M.A.W.P.	200 PSIG. @ 200 °F	CAD "B" SIZE UNDER "STD"-SERIES	
M.D.M.T.	-155 °F @ 200 PSIG.	BY: J.G.	
ASME. SECTION VIII	DIV. 1, 2010 ADD. 2010	SCALE: 1"=12"	
X-RAY:	RT-4 SPOT L.S. ONLY		
GALLONS:	120		
	WT. 409 LBS.		
SERIAL NO.			
N.B.			

ROY E. HANSON JR. MFG.
 1600 E. WASHINGTON BLVD.
 LOS ANGELES, CA 90021