



VIEW W/O SUPPORTS

2"R (10"R)  
W/ C.I. PLUG  
INSP. OPENING  
(2) PLC'S.

PLATFORM PER:  
SK-641 REV.4

NOTE: 1) HYDRO @ 325 PSIG. MIN.

HEADS	.164" SA-414-G 2:1 S.E.	HC-80-FP	REV. 3-21-13
JOGGLE	-.159" OFFSET (.136" MIN. REQ'D.)	FOR: HANSON STANDARD	DATE: 5-17-88
SHELL	.166" SA-414-G	HORIZ. AIR TANK	SURFACE AREA = 29.2 SQ. FT.
		INSIDE: UNPAINTED	
M.A.W.P.	250 PSIG. @ 400 °F	OUTSIDE: PRIME	
M.D.M.T.	-20 °F @ 250 PSIG.	CAD-"B" UNDER "STD"-SERIES	
ASME SECTION VIII	DIV. 1, 2010 ADD. 2011	BY: E.S.	SCALE: 1"=12"
X-RAY:	RT-NO	<b>ROY E. HANSON JR. MFG.</b>	
GALLONS:	80	1600 E. WASHINGTON BLVD.	
SERIAL NO.		LOS ANGELES, CA 90021	
N.B.			