



SHELL / HEADS	
JOGGLE	.166" SA-414-G 2:1 S.E.
M.A.W.P.	160 PSIG. @ 210 °F
ASME SECTION	IV 2013
X-RAY:	RT-NO / H.L.W.
GALLONS:	235 WT. 523 LBS.
SERIAL NO.	
N.B.	
<b>GS-30-235-V</b> REV. 2-26-16 FOR: HANSON STANDARD DATE: 2-28-90 VERT. WATER TANK SURFACE AREA = 58.0 SQ. FT. INSIDE: GLASS LINED OUTSIDE: S. BLAST & PRIME CAD "B" SIZE UNDER "STD" SERIES SF: 1.5 LEG-ZONE 4-15 KM. BY: E.S. SCALE: 1" = 12"	
<b>ROY E. HANSON JR. MFG.</b> 1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	

NOTE: 1) SHIP LOOSE W/ (1) 1 5/16" x 48" LG. FLEX MAG. ANODE.  
 2) 4-1-04 PROOF TEST.  
 3) HYDRO @ 240 PSIG.  
 4) CRN # 1623.7891

3/4"Ø SOLAR LIFT LUG (2) PLC'S.  
 2 1/2" B W/ LONG PILOT  
 1"-3000# FULL CPLG.  
 1 1/4"-3000# FULL CPLG. FOR ANODE  
 5/32" 5/32" TYP. CPLGS. & DRAIN  
 L.L.-N.S. & F.S.  
 12 TYP.  
 3 1/2"  
 3/4" B  
 150°  
 RAISED S.S. N.PL.  
 5.16 C/S  
 5.17 TYP.  
 30"  
 150°  
 1 1/4" R  
 3/4" B  
 2 1/2"  
 2 1/2"  
 14"  
 9"  
 4"  
 10 1/16"  
 4 1/4"  
 (3) 2 1/2" x 2 1/2" x 1/4" THK. x 19 15/16" LG. ANGLE LEGS  
 (3) 4" x 4" x 3/8" THK. PAD W/ 7/8" Ø HOLE  
 180°  
 2 1/2" R W/ LONG PILOT (2) PLC'S.  
 3/4"  
 15 11/16" @ 60° TYP.  
 7 7/8" @ 30° TYP.  
 1 1/4"  
 2 1/2"  
 90°  
 STD. BAFFLE 3 1/2" x 7" LG. 304 S.S.  
 11 L.S.  
 6"  
 0°