



LIQUID LEVEL	OT	79.8%
	HE	43 5/8"
C A L L I F	LI	56 3/4"
	FL	
SHELL / HEADS		
JOGGLED	.288" SA-612	2:1 S.E.
.289" OFFSET		
.337" SA-455		
M.A.W.P.	250 PSIG.	@ 200 °F
M.D.M.T.	-20 °F @	250 PSIG.
ASME. SECTION VIII	DIV.1, 2004 ADD. 2005	
X-RAY:	RT-4 SPOT L.S. & HDS. G.S.	
GALLONS:	1999	WT. 4523 LBS.
SERIAL NO.		
N.B.		

NOTE: 1) WELDS TO, OR JOINING SA-612 HAVE W.P.S. W/ SUFFIX "B".  
 2) INTERNAL PIPES PER PA-417-B-1B.  
 3) HYDRO @ 328 PSIG. MIN.

<b>PA-417-B</b>	REV. 10-26-06
FOR: HANSON STANDARD	DATE: 3-5-99
VERT. L.P.G. TANK.	
SURFACE AREA = 287.6 SQ. FT.	
C.F.M. REQ'D. = 5568	
INSIDE: UNPAINTED & DEHYDRATE	
OUTSIDE: PRIME	
LEG-ZONE 4-5 KM.	
BY: E.S.	SCALE: 1/2"=12"
<b>ROY E. HANSON JR. MFG.</b>	
1600 E. WASHINGTON BLVD.	
LOS ANGELES, CA 90021	

