



**VIEW W/O SUPPORTS**

NOTE: 1) HYDRO @ 262 PSIG. MIN.  
2) IMPACT TESTED? NO UG-20(f).

|                                |   |   |               |
|--------------------------------|---|---|---------------|
| SHELL / HEADS                  | .166" SA-414-G 2:1 S.E.<br>(.164" MIN.) | 30-HA-240-W                             | REV. 6-7-19   |
|                                | JOGGLE                                  |   | DATE: 12-1-87 |
|                                | .165" SA-414-G                          | FOR: HANSON STANDARD<br>HORIZ. AIR TANK |               |
| M.A.W.P.                       | 200 PSIG. @ 400 °F                      | INSIDE: UNPAINTED                       |               |
| M.D.M.T.                       | -20 °F @ 200 PSIG.                      | OUTSIDE: PRIME                          |               |
| ASME SECTION VIII DIV. 1, 2017 |   | CAD-"B" SIZE UNDER "STD"-SERIES         |               |
| X-RAY:                         | RT-4 SPOT L.S.                          | BY: J.A.                                | SCALE: 1"=12" |
| GALLONS:                       | 240                                     | WT. 499                                 | LBS.          |
| SERIAL NO.                     |   | <b>ROY E. HANSON JR. MFG.</b>           |               |
| N.B.                           |   | LOS ANGELES, CA 90021                   |               |