



304 S.S.-  
1/4" THK. CLIPS PER  
MA-395-B (4) PLC'S.  
W/ 9/16" ø HOLE ON  
26 3/8" B.C.; WELD OUTSIDE  
VERT. EDGE OF CLIP ONLY

- NOTE: 1) HYDRO @ 260 PSIG. MIN.  
2) ALL FNPT'S SA-182-304 S.S.  
3) UHA-51 (e)(2) NO IMPACT TESTING.  
4) 2"-R HAS 10"R.

SHELL / HEADS		.1875" SA-240-304 2:1 S.E.	
JOGGLE		30-VA-240-R	
		304 S.S.	
		FOR: HANSON STANDARD	
		VERT. AIR TANK	
		SURFACE AREA = 58.7 SQ. FT.	
		INSIDE: UNPAINTED-PASSIVATE	
M.A.W.P.	200 PSIG. @ 300 °F	OUTSIDE: BEAD BLAST & PASSIVATE	SCALE: 1" = 12"
M.D.M.T.	-155 °F @ 200 PSIG.	CAD "B" SIZE UNDER "STD" SERIES	BY: E.S.
ASME SECTION VIII DIV. 1, 2013		ROY E. HANSON JR. MFG.	
X-RAY: RT-4 SPOT L.S. ONLY		1600 E. WASHINGTON BLVD.	
GALLONS: 240	WT. 540 LBS.	LOS ANGELES, CA 90021	
SERIAL NO.			
N.B.			

REV. 12-1-14  
DATE: 7-11-06