



NOTE: 1) HYDRO @ 163 PSIG. MIN.

SHELL / HEADS	
JOGGLE	.182" SA-414-G 2:1 S.E.
	.165" SA-414-G
M.A.W.P.	125 PSIG. @ 180 °F
M.D.M.T.	0 °F @ 125 PSIG.
ASME SECTION VIII	DIV. 1, 2010 ADD 2010
X-RAY:	RT-NO
GALLONS:	285
SERIAL NO.	WT. 602 LBS.
N.B.	

NOTE: 1) HYDRO @ 163 PSIG. MIN.

FOR:	WN-147-B	REV:	
	VERT. HOT WATER TANK	DATE:	1-24-11
	SURFACE AREA = 61.8 SQ. FT.		
INSIDE:	EPOXY LINED		
OUTSIDE:	SHOP PRIME		
BY:	E.S. / C.J.	SCALE:	1" = 12"
	LEG-ZONE 4-10 KM.		
	<b>ROY E. HANSON JR. MFG.</b>		
	1600 E. WASHINGTON BLVD.		
	LOS ANGELES, CA 90021		

(3) 3"x 3"x 3/16" THK. x 21 1/8" LG. ANGLE LEGS

(3) 4"x 4"x 3/8" THK. PAD W/ 7/8" Ø HOLE FOR 5/8" Ø x 8" LG. BOLTS GRADE 5 OR BETTER 6" EMBEDMENT

