



DATE	BY
12-22-15	JG
3-10-16	JG
5-4-16	JG
5-19-16	JG
7-28-16	JG
8-15-16	JG

SHELL / HEADS	
.4375" SA-455	2:1 S.E.
(.372" MIN.)	
.375" SA-455	
.125" C.A. INTERNALS	
M.A.W.P. 150 PSIG. @ 180 °F	
M.D.M.T. -20 °F @ 150 PSIG.	
ASME SECTION VIII DIV. 1, 2015	
X-RAY: RT-2 SPOT G.S. & 100% L.S.	
GALLONS: 877	WT. 3213 LBS.
SERIAL NO.	
N.B.	

NOTE: 1) HYDRO @ 195 PSIG. MIN.  
 2) ALL FNPT'S NOT FLUSH INSIDE.  
 3) ROUND ALL INTERNAL SHARP EDGES.  
 4) NO B.U.B.-GRIND SMOOTH, NOT FLUSH.

WO-798-B	
REV. 8-15-16	DATE: 12-22-15
FOR: VERT. WATER/AIR TANK	
SURFACE AREA = 124.0 SQ. FT.	
UW-21(b)	
INSIDE: AMERLOCK 2 EPOXY	
(24 MILS TOTAL W/ HOLIDAY TEST)	
OUTSIDE: AMERLOCK 68HS,	
AMERLOCK 2 MID & GR-3 PEARL GREY	
AMERSHIELD TOP (15 MILS TOTAL)	
LEG-ZONE 4-15 KM.	
BY: E.S. / B.C.	SCALE: 3/4"=12"
<b>ROY E. HANSON JR. MFG.</b>	
LOS ANGELES, CA 90021	