



3) SHELL & LEFT HEAD - 8/26/04 PROOF TEST.  
 2) SHIP LOOSE W/(3) 1 5/16" x 60" LG. FLEX. MAG. ANODES.  
 NOTE. 1) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.

SHELL / HEADS	LEFT - .250" SA-455 2:1 S.E. (.210" MIN.)	GS-72-1950-H	REV. 8-26-11
	RIGHT - .317" SA-455 2:1 S.E. (.265" MIN.)		DATE: 5-21-90
	.250" SA-455	FOR: HANSON TANK	
		HORIZ. HOT WATER TANK. SURFACE AREA = 215.0 SQ.FT.	
		INSIDE: GLASS LINED	
	M.A.W.P. 125 PSIG. @ 210 °F	OUTSIDE: PRIME	
	ASME. SECTION IV 2010 ADD 2010	CAD "B" SIZE UNDER "STD"-SERIES	
	X-RAY: RT-NO/H.L.W.	BY: J.G. SCALE: 1/2"=12"	
	GALLONS: 1950 WT. 3138 LBS.	<b>ROY E. HANSON JR. MFG.</b>	
	SERIAL NO.	1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	
	N.B.		