



- 3) SHELL & LEFT HEAD - 8/26/04 PROOF TEST.
- 2) SHIP LOOSE W/ (5) 1 5/16" x 72" LG. FLEX. MAG. ANODES.
- NOTE. 1) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.

SHELL / HEADS	LEFT - .250" SA-455 2:1 S.E. (.210" MIN.)	GS-72-3500-H	REV. 3-24-14
	RIGHT - .289" SA-455 2:1 S.E. (.268" MIN.)		DATE: 10-8-09
	.252" SA-455	FOR: HANSON TANK	
		HORIZ. HOT WATER TANK.	
		SURFACE AREA = 359.2 SQ. FT.	
		INSIDE: GLASS LINED	
		OUTSIDE: S. BLAST, INORGANIC ZINC PRIME & R-16	
		CAD "B" SIZE UNDER "STD"-SERIES	
		BY: E.S.	SCALE: 1/2"=12"
		ROY E. HANSON JR. MFG.	
		1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	
	M.A.W.P. 125 PSIG. @ 210 °F		
	ASME. SECTION IV 2013		
	X-RAY: RT-NO / H.L.W.		
	GALLONS: 3500	WT. 4938	LBS.
	SERIAL NO.		
	N.B.		