



| | |
|----------------------------|----------------|
| SHELL / HEADS | |
| .205" SA-455 | 2:1 S.E. |
| JOGGLE | |
| .189 OFFSET - BROWN STRIPE | |
| .175" SA-414-G | |
| M.A.W.P. 160 | PSIG. @ 180 °F |
| ASME. SECTION IV | 2004 ADD 2006 |
| X-RAY: RT-NO / H.L.W. | |
| GALLONS: 660 | WT. 1065 LBS. |
| SERIAL NO. | |
| N.B. | |

NOTE: 1) 4-1-04 PROOF TEST.
2) HYDRO @ 240 PSIG.

| | |
|---|-----------------|
| ES-42-660-V | |
| REV. 1-22-07 | DATE: 9-6-89 |
| FOR: HANSON STANDARD | |
| VERT. HOT WATER TANK | |
| SURFACE AREA = 115.8 SQ. FT. | |
| INSIDE: EPOXY LINED | |
| OUTSIDE: PRIME | |
| CAD "B" SIZE UNDER "STD"-SERIES | |
| LEG-ZONE 4-15KM. | |
| BY: J.G. | SCALE: 3/4"=12" |
| ROY E. HANSON JR. MFG. | |
| 1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021 | |

