



- 4) 8-26-04 PROOF TEST.
- 3) 6" COLLAR SA-312-304 E.R.W.
- 2) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.
- NOTE. 1) SHIP LOOSE W/ (3) 1 5/16" x 72" LG. FLEX. MAG. ANODES

HEADS	.289" SA-455 2:1 S.E.	WM-483-B	REV. 10-24-08
	RIGHT - .264" MIN.		DATE: 10-14-08
	LEFT - .222" MIN.		
SHELL		FOR: -	
		HORIZ. HOT WATER TANK	
	.250" SA-455	SURFACE AREA = 215.0 SQ. FT.	
		INSIDE: GLASS LINED	
	M.A.W.P. 125 PSIG. @ 210 °F	OUTSIDE: S. BLAST, PRIME	
	ASME. SECTION IV 2007 ADD 2007		
	X-RAY: RT-NO / H.L.W.	BY: E.S. / C.J.   SCALE: 1/2"=12"	
	GALLONS: 1950   WT. 3240 LBS.	<b>ROY E. HANSON JR. MFG.</b>	
	SERIAL NO.	1600 E. WASHINGTON BLVD.	
	N.B.	LOS ANGELES, CA 90021	

VIEW W/O SUPPORTS

6" COLLAR DTL.