



VIEW W/O SUPPORTS

3) ALL PIPES SA-312-304 E.R.W.  
 2) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.  
 NOTE: 1) SHIP LOOSE W/ (6) 1 5/16" x 60" LG. FLEX. MAG. ANODES.

|                                |   |   |                              |
|--------------------------------|---|---|------------------------------|
| HEADS / SHELL                  | LEFT - .250" SA-455 2:1 S.E.<br>(.219" MIN.)  | WM-530-B  | REV. 12-9-08                 |
|                                | RIGHT - .289" SA-455 2:1 S.E.<br>(.246" MIN.) |   | DATE: 11-26-08               |
|                                | ENDS - .289" SA-455 @ 72"                     |   | FOR: -                       |
|                                | CENTER - .250" SA-455 @ 94"                   |   | HORIZ. HOT WATER TANK        |
|                                |   |   | SURFACE AREA = 410.0 SQ. FT. |
| M.A.W.P. 125 PSIG. @ 210 °F    |   | INSIDE: GLASS LINED                               |                              |
| ASME. SECTION IV 2007 ADD 2007 |   | OUTSIDE: PRIME                                    |                              |
| X-RAY: RT-NO / H.L.W.          |   | BY: E.S. / C.J.   SCALE: 3/8"=12"                 |                              |
| GALLONS: 3800                  | WT. 6270 LBS.                                 | <b>ROY E. HANSON JR. MFG.</b>                     |                              |
| SERIAL NO.                     |   | 1600 E. WASHINGTON BLVD.<br>LOS ANGELES, CA 90021 |                              |
| N.B.                           |   |   |                              |