



- 5) 8-26-04 PROOF TEST.
 4) ALL PIPES SA-312-304 ERW S.S.
 3) SHIP LOOSE W/ (2) 1 5/16" x 72" LG. FLEX. MAG. ANODES.
 2) SHIP LOOSE W/ (1) 1 5/16" x 60" LG. FLEX. MAG. ANODES.
 NOTE: 1) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.

SHELL/HEADS	.250" SA-455 2:1 S.E. (.219" MIN.)	WN-174-B	REV. 2-24-11	
	.252" SA-455		DATE: 2-22-11	
	FOR: -		HORIZ. HOT WATER TANK	
	M.A.W.P. 125 PSIG. @ 210 °F		SURFACE AREA = 236.0 SQ. FT.	
ASME. SECTION IV 2010 ADD. 2010		INSIDE: GLASS LINED		
X-RAY: RT-NO / H.L.W.		OUTSIDE: S. BLAST, PRIME		
GALLONS: 2150 WT. 3362 LBS.		BY: J.G./C.J. SCALE: 1/2" = 12"		
SERIAL NO.		ROY E. HANSON JR. MFG. 1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021		
N.B.				