



- NOTE: 1) HYDRO @ 195 PSIG. MIN. - 1999 ADDENDA.  
 2) SEISMIC ZONE 2-B  
 3) PREHEAT BEFORE WELDING TO 150 °F.  
 4) INORGANIC ZINC PRIME, (4) MILS EPOXY AND 3-4 MILS POLYURETHANE GRAY.  
 5) COVER ALL OPENINGS FOR SHIPPING.

SHELL / HEADS	
.625" SA-516-70 2:1 S.E. (.510" MIN.)	AG-539-C REV. 7/27/00 DATE: 6/28/00
.625" SA-516-70	
.0625" C.A. ON ENTIRE VESSEL	
M.A.W.P. 150 PSIG. @ 200 °F.	
M.D.M.T. -20 °F @ 150 PSIG.	
ASME SECTION VIII DIV. 1, 1998 ADD 1999	
X-RAY: RT-4 SPOT L.S. & HD. G.S.	
GALLONS: 15,100 WT. 28,189 LBS.	
SERIAL NO.	
N.B.	
VERT. AIR TANK	
INTEL OCC2-TK-212-1-210 &	
INTEL OCC2-TK-212-2-210	
INSIDE: EPOXY LINED (2) COATS MIN.	
SURFACE AREA = 929.0 SQ. FT.	
OUTSIDE: S.BLAST EPOXY FOR EXT. USE	
SEE NOTE: 4	
SURFACE AREA = 1063.4 SQ. FT.	
BY: J.G. / BILL SCALE: 3/8"=12"	
<b>ROY E. HANSON JR. MFG.</b>	
1924 COMPTON AVE.	
LOS ANGELES, CA 90011	