



GALLONS (GROSS)	DIA. A	LENGTH B	SUPPORTS C	LIQUID LEVEL		MANWAY SIZE
				"F"	"E"	
250	30"	84"	53"	6 1/4"	17 5/16"	11"x15"
400	36	98	56	7 1/2"	20 3/4"	11"x15"
500	36	119	76	7 1/2"	20 3/4"	11"x15"
660	42	120	76	8 3/4"	24 1/4"	12"x16"
1060	48	144	94	10"	27 11/16"	12"x16"
1550	54	168	115	11 1/4"	31 3/16"	12"x16"
2180	60	192	137	12 1/2"	34 11/16"	12"x16"
2520	60	220	164	12 1/2"	34 11/16"	12"x16"
3000	66	216	138	13 3/4"	38 1/8"	12"x16"
3800	72	232	156	15 1/2"	41 9/16"	12"x16"
5000	84	226	124	17 1/2"	48 1/2"	12"x16"
10000	96	341	188	20"	55 1/2"	12"x16"
15000	96	503	277	20"	55 1/2"	12"x16"

COATING OPTIONS	
INTERIOR	EXTERIOR
EPOXY - PLASITE 7156	WIRE BRUSH, SHOP PRIME, FINISH ENAMEL
GLASS - PORCELAIN ENAMEL WITH ANODES	SAND BLAST, INORGANIC ZINC, EPOXY PRIME, FINISH ENAMEL

LIQUID	LEVEL
DIA. x .208 = "F"	15% FULL
DIA. x .577 = "E"	60% FULL

WK-864-B	REV. 12-14-20
	DATE: 12-5-15
HYDRO PNEUMATIC TANKS	
125 PSIG. WORKING PRESSURE	
INTERIOR: CUSTOMER OPTION	
OUTSIDE: PAINTED MACHINERY GREY	
ROY E. HANSON JR. MFG.	
LOS ANGELES, CA 90021	