



- NOTE. 1) HYDRO @ 390 PSIG. MIN.
2) 6" FLG. & CPLG'S SA-182-304 S.S.
3) 6" PIPE SA-312-304 SMLS.
4) ALL CPLG'S INSIDE FLUSH.
5) BRASS PLUG ALL NOZZLE FOR SHIPPING.

MARK: BOTTOM TANK "B"
SEE AH-667-B-2B FOR STACKING DETAIL

HEADS	.625" SA-516-70 2:1 S.E. (.533" MIN.)
SHELL	.625" SA-516-70
M.A.W.P.	300 PSIG. @ 200 °F
M.D.M.T.	-20 °F @ 300 PSIG.
ASME. SECTION VIII DIV. 1, 2007 ADD 2009	
X-RAY: RT-2 100% L.S., SPOT ALL G.S.	
GALLONS:	3625
WT.	12104 LBS.
SERIAL NO.	
N.B.	

AH-667-B	REV. 3-10-10
	DATE: 3-3-10
FOR:	
HORIZ. BREATHING AIR TANK.	
SURFACE AREA = 375.6 SQ.FT.	
UW-21 (b)	
INSIDE: S.BLAST AND AQUAPON POLY EPOXY (2) PART	
OUTSIDE: S.BLAST AND AQUAPON POLY EPOXY (2) PART	
BY: J.G./R.L.	SCALE: 1/2"=12"
ROY E. HANSON JR. MFG.	
1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	