



GENERAL NOTES

- | | | |
|---|---------------------------------------|--|
| 1. SHELL: <u>.338" SA-455</u> | 7. M.A.W.P. <u>250 PSIG. @ 200 °F</u> | 13. C.F.M. REQ'D. <u>2089.3</u> |
| 2. HEADS: <u>.288" SA-455 2:1 S.E. JOGGLE - .298 OFFSET</u> | M.D.M.T. <u>0 °F @ 250 PSIG.</u> | 14. OUTSIDE: <u>S. BLAST, PRIME & WHITE ENAMEL</u> |
| 3. X-RAY: <u>RT-4 SPOT L.S. & HEAD G.S.</u> | 8. HYDRO: <u>327 PSIG. MIN.</u> | |
| 4. STRESS REL., <u>NO</u> | 9. GAL: <u>497</u> | |
| 5. CORR. ALLOW: <u>NONE</u> | 10. EMPTY WT: <u>1269# APROX.</u> | |
| 6. ASME SEC. <u>VIII</u> DIV. 1, 2007 ADD 2009 | 11. <u>DEHYDRATE INSIDE</u> | |
| | 12. SURFACE AREA: <u>87.0 SQ. FT.</u> | |

PA-871-B	REV.
	DATE: 8-24-10
FOR:	
HORIZ. LPG TANK	
BY: J.G./C.J.	SCALE: 1/2"=12"
ROY E. HANSON JR. MFG.	
1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	